

19



Europäisches Patentamt
European Patent Office
Office européen des brevets

11 Veröffentlichungsnummer:

11 Publication number:

11 Numéro de publication:

0 793 614

Internationale Anmeldung veröffentlicht durch die
Weltorganisation für geistiges Eigentum unter der Nummer:

WO 96/15974 (art.158 des EPÜ).

International application published by the World
Intellectual Property Organisation under number:

WO 96/15974 (art.158 of the EPC).

Demande internationale publiée par l'Organisation
Mondiale de la Propriété sous le numéro:


WO 96/15974 (art.158 de la CBE).

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B66B 9/08	A1	(11) International Publication Number: WO 96/15974 (43) International Publication Date: 30 May 1996 (30.05.96)
<p>(21) International Application Number: PCT/NL95/00401</p> <p>(22) International Filing Date: 23 November 1995 (23.11.95)</p> <p>(30) Priority Data: 9401963 23 November 1994 (23.11.94) NL</p> <p>(71) Applicant (for all designated States except US): TRAPLIFT B.V. [NL/NL]; Gronausestraat 35, NL-7533 BW Enschede (NL).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): LAMMERS, Evert, Jan [NL/NL]; Gronausestraat 35, NL-7533 BW Enschede (NL).</p> <p>(74) Agent: SCHUMANN, Bernard, Herman, Johan; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).</p>	<p>(81) Designated States: AL, AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Dutch).</i></p>	

(54) Title: **STAIRLIFT**

(57) Abstract

A stairlift comprises: a main frame (23); support means for supporting this main frame such that it is movable along a support rail (4) which is arranged at some height thereabove along a staircase; a first electric motor (22) for moving the main frame along the support rail; and an auxiliary frame (25) supported by the main frame for carrying a chair, for example a wheelchair, via a support platform such that the auxiliary frame is movable and fixable relative to the main frame by three auxiliary electric motors in two rotation degrees of freedom and one translation degree of freedom.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

STAIRLIFT

The invention relates to a stairlift. Such a stairlift is known. A known stairlift has the drawback that the support rail must be placed with great precision and care while avoiding inaccuracies in the angle of inclination, since otherwise the accuracy of the position of the stairlift can depend on its location along the path.

It is an object of the invention to embody a stairlift such that it can function with excellent positional accuracy, even in cases where the support rail has been arranged with relatively little accuracy of positioning.

According to the invention this object is achieved with a stairlift comprising:

- 15 a main frame;
- support means for supporting this main frame such that it is movable along a support rail, which is arranged at some height thereabove along a staircase;
- a first electric motor for moving the main
- 20 frame along the support rail; and
- an auxiliary frame supported by the main frame for carrying a chair, for example a wheelchair, via a support platform, such that the auxiliary frame is movable and fixable relative to the main frame by three
- 25 auxiliary electric motors in two rotation degrees of freedom and one translation degree of freedom.

Such a stairlift can have the special feature that the first rotation degree of freedom is intended for up and downward pivoting of the auxiliary frame on a first, at least more or less horizontally extending axis. This first axis can advantageously extend in a plane which coincides with, or is located a short distance from, the main plane of the seat of a chair or wheelchair.

Another special feature of the stairlift can lie in the fact that the second rotation degree of freedom is intended for pivoting the auxiliary frame round a second axis extending substantially transversely of the rail and at least more or less in horizontal direction. This second axis will preferably extend in the median plane of a chair or wheelchair and extend in the main plane of the seat or at a distance thereunder.

Said last two special features can be combined in a variant wherein the first and the second axis are at least more or less intersecting. In this embodiment the two rotation degrees of freedom extend substantially in one plane. The cardan mobility of the auxiliary frame determined by these degrees of freedom ensures a complete adaptability to any angle of inclination defined by the support rail.

The stairlift is further embodied such that it is able to displace in the translation degree of freedom such that a user effectively avoids contact with obstacles. In particular such an embodiment can display the feature that the translation degree of freedom is intended for moving the chair up and downward.

The simplest possible control is ensured with an embodiment in which the three said degrees of freedom are mutually independent.

The stairlift is preferably provided with a battery. This battery is arranged for example on the main frame or the chair, in any case is movable together with the stairlift. The use of cables or drag connections is hereby avoided.

In order to always keep the battery in optimum charged state or to restore the charged state as required, the embodiment is recommended in which on at least one end of the support rail is placed a terminal of a charging device which can co-act with a complementary terminal which is present on the stairlift and which is connected to the battery for charging the battery in the coupled state of said terminals.

A practical embodiment displays the special feature that the first electric motor drives a toothed wheel which can co-act with a toothing arranged on the support rail, for instance a cardan fixed chain supported thereby. The use of a cardan fixed chain offers the option of following not only variations of angle in a vertical plane but also variations of angle in a horizontal plane.

The stairlift is preferably provided with a central control unit for operating by a user. For this purpose use can be made for example of a control unit bearing a plurality of control buttons which is arranged in an arm of the chair.

The stairlift preferably has the special feature that the central control unit is of the self-learning type. This latter embodiment has the advantage that the position adjustment in each of the three degrees of freedom does not have to be programmed in advance depending on the current position of the stairlift, but that through a learning process these positions for a given path of the support rail are automatically followed by the system. In the learning phase it can for example be ensured by external means that during use the chair is situated in each position along the path such that the seat is for instance situated in a substantially horizontal position or displays a selected variation therefrom. A suitable position can be programmed for stepping in and out at both end locations.

The invention will now be elucidated with reference to the annexed drawings, in which:

figure 1 shows a schematic perspective view of a stairlift according to the invention; and

figure 2 shows a partly broken away perspective view on enlarged scale of that part of the stairlift into which the invention is incorporated.

Figure 1 shows a staircase 1 consisting of a plurality of parts, which is bounded on one side by walls 2. A support rail 4 consisting of segments is fixed to

these walls by means of support bolts 3. For the sake of an optimal mechanical strength and safety this support rail 4 is further supported by supports 5 which rest with joint foot plates 6 on the treads 7 of the staircase.

5 As figure 1 shows, the stairlift carries a chair 8 with a seat 9 and a back 10, and a footrest 11 supported by the seat. As will be elucidated below with reference to figure 2, the chair is supported such that it is movable in three degrees of freedom.

10 The first degree of freedom is a rotation degree of freedom, which is indicated with reference numeral 12. In this rotation degree of freedom the chair 8 is pivotable up and downward round an axis 13.

15 In a second rotation degree of freedom 14 the chair 8 is pivotable round an axis 15.

20 In a third degree of freedom, a translation, the chair 8 is movable up and downward. This movement is not strictly vertical but has a vertical component. This degree of freedom is designated in the drawing with the reference numeral 16.

25 As is shown clearly in figure 1, the position of the support rail 4 is greatly variable along its length. The three degrees of freedom of the stairlift according to the invention enable full adaptation thereof. The position variations of the chair 9 are compensated by the rotation degrees of freedom 12 and 14, while the height adjustment is provided by the third degree of freedom 16. This may for instance be necessary to avoid contact between the head of a user and a relatively low ceiling edge 17. Use is made for this purpose of a motor 43 with output spindle shaft 44 which co-acts with a wire (not drawn) present in the block 32.

30 Figure 2 shows that the support rail 4 is open on the underside and supports a cardan linked chain 18. 35 Through driving of the stairlift 19 this chain can co-act with a toothed wheel 20 which is driven by an electric motor 22 via a worm transmission 21. This electric motor 22 is of a relatively heavy type, since it must be

capable of carrying the entire weight of a user and the stairlift 19 upward along the support rail 4. The motor 22 is supported by a main frame 23 which is rollable along support rail 4 by means of rollers generally designated 24.

The main frame 23 supports via an axis 13 an auxiliary frame 25 by means of an electric motor 26 which can drive a threaded spindle 27 and the position of auxiliary frame 25 is adjustable relative to the main frame 23. For this purpose the spindle 27 co-acts with a tube 28 provided with internal thread which co-acts pivotally with a bracket 29 which is connected to an auxiliary frame 25 via sliding rods 30,31. The sliding rods 30,31 serve for slidable guiding of a support block 32 which bears a support shaft 33 rotatably round an axis 15. Supports 34 for the chair 8 are connected to support shaft 33. To the support shaft 33 is connected a toothed bracket 35 which co-acts with a toothed wheel driven by an electric motor 36. By driving the motor 36 the chair 8 can be pivoted round the axis 15. The folding arm-rest 38 carries a control panel 39.

It has not been shown that the stairlift 19 carries rechargeable batteries. Figure 1 shows that a terminal 40 is fixed to the seat of the chair which can co-act with terminals 41,42 of a charging device arranged at the ends of the support rail. The batteries can hereby be recharged in the end positions of the stairlift.

X Sch/EN/1

CLAIMS


1. Stairlift, comprising:
a main frame;
support means for supporting this main frame
such that it is movable along a support rail which is
5 arranged at some height thereabove along a staircase;
a first electric motor for moving the main
frame along the support rail; and
an auxiliary frame supported by the main frame
for carrying a chair, for example a wheelchair, via a
10 support platform such that the auxiliary frame is movable
and fixable relative to the main frame by three auxiliary
electric motors in two rotation degrees of freedom and
one translation degree of freedom.
2. Stairlift as claimed in claim 1, wherein the
15 first rotation degree of freedom is intended for up and
downward pivoting of the auxiliary frame on a first, at
least more or less horizontally extending axis.
3. Stairlift as claimed in claim 1, wherein the
20 second rotation degree of freedom is intended for
pivoting the auxiliary frame round a second axis
extending substantially transversely of the rail and at
least more or less in horizontal direction.
4. Stairlift as claimed in claims 2 and 3,
25 wherein the first and the second axis are at least more
or less intersecting.
5. Stairlift as claimed in claim 1, wherein the
translation degree of freedom is intended for moving the
auxiliary frame up and downward.
6. Stairlift as claimed in claim 1, wherein the
30 three said degrees of freedom are mutually independent.
7. Stairlift as claimed in claim 1, comprising
a battery.
8. Stairlift as claimed in claim 1, wherein on
at least one end of the support rail is placed a terminal

for a charging device which can co-act with a complementary terminal which is present on the stairlift and which is connected to the battery for charging the battery in the coupled state of said terminals.

5 9. Stairlift as claimed in claim 1, wherein the first electric motor drives a toothed wheel which can co-act with a toothing arranged on the support rail, for example a cardan fixed chain supported thereby.

10 10. Stairlift as claimed in claim 1, comprising a central control unit for operating by a user.

11. Stairlift as claimed in claim 10, wherein the central control unit is of the self-learning type.



INTERNATIONAL SEARCH REPORT

Int'l Application No
PCT/NL 95/00401

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 B66B9/08		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) IPC 6 B66B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 560 433 (LIFTENFABRIEK BRINKMAN JAN HAMER B.V.) 15 September 1993 see column 3, line 1 - line 44 ---	1
A	US,A,5 165 753 (HENDERSON ELDRED D) 24 November 1992 see abstract ---	2
A	US,A,5 230 405 (BARTELT ROBERT D) 27 July 1993 see abstract ---	7,8
A	US,A,4 904 916 (GISSKE EDWARD T ET AL) 27 February 1990 see abstract -----	10,11
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 8 March 1996		Date of mailing of the international search report 27.03.1996
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax (+ 31-70) 340-3016		Authorized officer Sozzi, R

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No


PCT/NL 95/00401


Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-560433	15-09-93	NL-A- 9200437	01-10-93
US-A-5165753	24-11-92	NONE	
US-A-5230405	27-07-93	NONE	
US-A-4904916	27-02-90	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)

THIS PAGE BLANK (USPTO)

1/2





**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)